

K 855

INDUSTRIAL THREE-PHASE DRY VACUUM CLEANERS

Industrial dry vacuum cleaner equipped with a 7.5 hp induction motor. 6-stage turbine with fans of 267 mm diameter. Manual filter shaking system. Fast detachable tank mounted on trolley. HEPA cartridge filter optional. Version "Com B.T." equipped with 24 V safety voltage. It can be used as a blower. Delivered without accessories, must be ordered separately.



Lever system



Filter shaker



Waterproof switches

PRODUCT IDENTIFICATION

TYPE

K 855 HP 7,5 380 V
K 855 HP 7,5 Com.B.T.

REF. NO.

00-17200101
00-17200121

PIECES/PALLET

1
1

TECHNICAL DATA

Voltage - Frequency	400 V ³ ~ 50 Hz
Max power rating	W 5500
Rated power (nominal power)	W 5500
Container capacity	l 60
Useful capacity	l 60
Filtering surface	m ² 1,2
Air flow rate	l/s 135
Vacuum	mbar 300
Sound level	db(A) 70
IP code	IPX4
Power supply cable	m 10
Weight (without accessories)	Kg 120
Dimensions	mm 1200 x 600 x 1300

STANDARD ACCESSORIES

Ø 50

TYPE

Textile filter

REF. NO.

20-583

OPTIONAL ACCESSORIES

TYPE

Flexible hose 3 m
Reduction 90-50
PVC extension tube 0,5 m
Curved suction tube
Adjustable dry brush 0,5 m
Round brush
Crevice tool
PVC reduction Ø 50
Nylon filter (filtering surface 0,7 m²)
HEPA Cartridge filter (filtering surface 0,9 m²)

REF. NO.

01-510
01-561
2512021
2511700
6010062
2511720
2511730
2511710
20-564
20-566